



Timeless natural hues

N° 1021454

FLAMED BEECH BOIS FLOTTÉ, HERRINGBONE 139 TONGUE&GROOVE / 14 MM

Characteristics

Specie: Beech **Origin:** France

Grade: - Flamed red wood, light and dark wood, knots, all peculiarities accepted.

Finish: Bois flotté - brushed, matt lacquered with unfinished aspect / Ecostrong matt lacquer - Gloss: 4/6

Design

Engineered single plank herringbone made under the patent EN 13489
 Tongue&Groove

Description

- Width:** 139 mm
- Length:** 800 mm
- Thickness:** 14 mm
- Top layer:** 3.4 mm
- Core:** plywood
- Counterbalance:** unrolled wood
- Profile:** 4 bevels

Packaging

- sqm/pack:** 2.22
- Pack/pallet:** 32
- sqm/pallet:** 71.04
- Weight/sqm:** 7.4 kg
- Weight/pallet:** 525.7 kg



Installation method





Floating glued
 installation under the
 patent DTU 51.11



Glue down installation
 under the patent DTU 51.2



Collage en plein avec presto PM
 unquement.





DECLARATION OF PERFORMANCE

N° 1021454

Unique identification code of product-type: Herringbone 139 Tongue&Groove, 14 mm, Beech

Intended use/es: Engineered single plank made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

| Essential features | Performances | Appropriate Technical Documentation and/or Specific Technical Documentation | |
|---|--|---|----------|
| Reaction of fire | Dfl-s1 | EN 14342 : 2013 | |
| Features for this classification: - Average minimum density (Kg/m ³) - Average thickness (mm) - Intended use, fitting mode | 500 14 Floating fit | | |
| Formaldehyde emission | E1 | | EN 717-1 |
| Content of pentachlorophenol | PCP ≤ 5 ppm | | - |
| Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEV0910046A) | Class A+ < 1µg/m ³ | ISO 16000 | |
| Breaking strength | N/A | - | |
| Slipperiness | N/A | - | |
| Thermal conductivity (W/m.K) | 0.13 | EN 14342 / Chapter 4.7 | |
| Thermal resistance (m ² .K/W) | 0.108 | | |
| Biological sustainability | Class 1 | EN 335 | |
| RE2020 - Building Carbon Index | 3 kg.CO ₂ /m ² | - | |
| FDES 2022 - Life Cycle impact assessment | 8.6 kg éq. CO ₂ /m ² | - | |

N/A : Not Applicate

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025

Carole FRANÇOIS