



Timeless natural hues

N° 1016985

## FRENCH OAK AUTHENTIC BOIS FLOTTÉ, DIVA 223 TONGUE&GROOVE / 15 MM

### Characteristics

**Specie:** French oak **Origin:** France

**Grade: Authentic** - Light and dark wood, black knots, filled knots, partially opened knots, traces of discolouration, black marks, cracks. This size of the knots is proportional to the width of the planks.

**Finish: Bois flotté** - brushed, matt lacquered with unfinished aspect / Ecostrong matt lacquer - Gloss: 4/6

### Design

Engineered extra-wide single plank made under the patent EN 13489  
Tongue&Groove



### Description

**Width:** 223 mm  
**Length:** 700 to 2000 mm  
**Thickness:** 15 mm  
**Top layer:** 4.5 mm  
**Core:** plywood  
**Counterbalance:** unrolled wood  
**Profile:** 2 bevels

### Packaging

**sqm/pack:** 1.78  
**Pack/pallet:** 39  
**sqm/pallet:** 69.42  
**Weight/sqm:** 10.9 kg  
**Weight/pallet:** 756.7 kg



### Installation method





Floating Glued  
installation under the  
patent DTU 51.11



Glue down installation  
under the patent DTU 51.2



Fully glue down using our  
special Presto PM glue.



# DECLARATION OF PERFORMANCE

## N° 1016985



**Unique identification code of product-type:** Diva 223 Tongue&Groove, 15 mm, French oak

**Intended use/es:** Engineered single plank made under the patent EN 13489

Floating Glued installation under the patent DTU 51.11

**Manufacturer:** PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

**System/s of Assessment and Verification of Constancy of Performance:** n°4

**Harmonised standard:** EN 14342 : 2013

### Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation	
Reaction of fire	Dfl-s1	EN 14342 : 2013	
Features for this classification: - Average minimum density (Kg/m <sup>3</sup> ) - Average thickness (mm) - Intended use, fitting mode	500 15 Floating fit		
Formaldehyde emission	E1		EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm		-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVPO910046A)	Class A+ < 1µg/m <sup>3</sup>	ISO 16000	
Breaking strength	N/A	-	
Slipperiness	N/A	-	
Thermal conductivity (W/m.K)	0.15	EN 14342 / Chapter 4.7	
Thermal resistance (m <sup>2</sup> .K/W)	0.100		
Biological sustainability	Class 1	EN 335	
RE2020 - Building Carbon Index	3 kg.CO <sub>2</sub> /m <sup>2</sup>	-	
FDES 2022 - Life Cycle impact assessment	8.6 kg éq. CO <sub>2</sub> /m <sup>2</sup>	-	

N/A : Not Applicate

\*VOC: Volatile Organic Compounds

\*\*CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025  
**Carole FRANÇOIS**

