



Timeless natural hues

PANAGET

manufacture française de parquet
DEPUIS 1929



N° 1005735

FRENCH OAK CLASSIC TOPAZE, CHEVRON 90 TONGUE&GROOVE / 14 MM

Characteristics

Specie: French oak **Origin:** France

Grade: Classic - Light and dark wood, black knots, medular rays, traces of discolouration.

Finish: Topaze - brushed, matt lacquered / Ecostrong matt lacquer - Gloss: 4/6

Design

Engineered single plank chevron made under the patent EN 13489
Tongue&Groove

Description

Width: 90 mm
Length: 500 mm
Thickness: 14 mm
Top layer: 3.4 mm
Core: plywood
Counterbalance: unrolled wood
Profile: 4 bevels

Packaging

sqm/pack: 1.26
Pack/pallet: 32
sqm/pallet: 40.32
Weight/sqm: 7.4 kg
Weight/pallet: 298.4 kg



if installation and
maintenance rules are
followed



Installation method



Floating glued
installation under the
patent DTU 51.11




Glue down installation
under the patent DTU 51.2



Floating installation gluing TG
using plastic DPM and Isol 20 or
fully glue down using Presto PM



*Emissions of volatile substances which could be
toxic if inhaled. These are rated on scale from A+
(very low) to C (high).



PANAGET - 3 rue d'Orgères - 35230 Bourgarré - FRANCE
tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // www.panaget.com

DECLARATION OF PERFORMANCE

N° 1005735



Unique identification code of product-type: Chevron 90 Tongue&Groove, 14 mm, French oak

Intended use/es: Engineered single plank made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

| Essential features | Performances | Appropriate Technical Documentation and/or Specific Technical Documentation | |
|---|--|---|----------|
| Reaction of fire | Dfl-s1 | EN 14342 : 2013 | |
| Features for this classification: - Average minimum density (Kg/m ³) - Average thickness (mm) - Intended use, fitting mode | 500 14 Floating fit | | |
| Formaldehyde emission | E1 | | EN 717-1 |
| Content of pentachlorophenol | PCP ≤ 5 ppm | | - |
| Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A) | Class A+ < 1µg/m ³ | ISO 16000 | |
| Breaking strength | N/A | - | |
| Slipperiness | N/A | - | |
| Thermal conductivity (W/m.K) | 0.13 | EN 14342 / Chapter 4.7 | |
| Thermal resistance (m ² .K/W) | 0.108 | | |
| Biological sustainability | Class 1 | EN 335 | |
| RE2020 - Building Carbon Index | 3 kg.CO ₂ /m ² | - | |
| FDES 2022 - Life Cycle impact assessment | 8.6 kg éq. CO ₂ /m ² | - | |

N/A : Not Applicate

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025

Carole FRANÇOIS

