



Timeless natural hues

PANAGET

manufacture française de parquet
DEPUIS 1929



N° 1006920

FRENCH OAK TRADITION SATIN, ORFÉO 139 CLICK / 14 MM

Characteristics

Specie: French oak **Origin:** France

Grade: Tradition - Light and dark wood, black knots, filled knots, partially opened knots, traces of discoloration, black marks, filled cracks, sapwood.

Finish: Satin - unbrushed, satin lacquered / Ecostrong satin lacquer - Gloss: 28/32

Design

Engineered two-strip made under the patent EN 13489
Click made under Unilin patent n°EP1640530

Description

Width: 139 mm
Length: 1500 mm
Thickness: 14 mm
Top layer: 3.4 mm
Core: HDF*
Counterbalance: unrolled wood
Profile: square edged

*High Density Fiber board

Packaging

sqm/pack: 1.46
Pack/pallet: 50
sqm/pallet: 73.00
Weight/sqm: 11.8 kg
Weight/pallet: 861.4 kg



if installation and
maintenance rules are
followed



Installation method



Glue-free floating under
the patent DTU 51.11



Glue down installation
under the patent DTU 51.2




Floating installation using
plastic DM and Isol 20 or fully
glue down using Presto PM



Fully glue down Presto PM



*Emissions of volatile substances which could be toxic if inhaled. These are rated on scale from A+ (very low) to C (high).



PANAGET - 3 rue d'Orgères - 35230 Bourgbarré - FRANCE
tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // www.panaget.com

DECLARATION OF PERFORMANCE

N° 1006920



Unique identification code of product-type: Orféo 139 Click, 14 mm, French oak

Intended use/es: Engineered single plank made under the patent EN 13489

Glue-free floating under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation
Reaction of fire	Dfl-s	EN 14342 : 2013
Features for this classification:		
- Average minimum density (Kg/m ³)	500	
- Average thickness (mm)	14	
- Intended use, fitting mode	Floating fit	
Formaldehyde emission	E1	EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm	-
Release of other dangerous substances:		ISO 16000
- VOC* emissions (Decree No 2011-321)	Class A+	
- CMR 1&2** emissions (Decree No DEVP0910046A)	< 1 µg/m ³	
Breaking strength	N/A	-
Slipperiness	N/A	-
Thermal conductivity (W/m.K)	0.15	EN 14342 / Chapter 4.7
Thermal resistance (m ² .K/W)	0.093	
Biological sustainability	Class 1	EN 335
RE2020 - Building Carbon Index	3 kg.CO ₂ /m ²	-
FDES 2022 - Life Cycle impact assessment	8.6 kg éq. CO ₂ /m ²	-

N/A : Not Applicable

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025

Carole FRANÇOIS

