



Timeless natural hues

N° 1019824

## FRENCH OAK ZENITUDE MIEL, CHEVRON 139 TONGUE&GROOVE / 14 MM

### Characteristics

**Specie:** French oak **Origin:** France

**Grade: Zenitude** - Light and dark wood, black knots, filled knots, partially opened knots, traces of discolouration, cracks, splits, heartwood, sapwood. Grade with all peculiarities of the wood without limitation. The size of the knots is proportional to the width of the planks.

**Finish: Miel** - brushed, natural matt lacquered / Ecostrong matt lacquer - Gloss: 4/6

### Design

Engineered single plank chevron made under the patent EN 13489  
 Tongue&Groove

### Description

**Width:** 139 mm  
**Length:** 650 mm  
**Thickness:** 14 mm  
**Top layer:** 3.4 mm  
**Core:** plywood  
**Counterbalance:** unrolled wood  
**Profile:** 4 bevels

### Packaging

**sqm/pack:** 1.45  
**Pack/pallet:** 32  
**sqm/pallet:** 46.40  
**Weight/sqm:** 7.4 kg  
**Weight/pallet:** 343.4 kg



### Installation method





Floating glued  
 installation under the  
 patent DTU 51.11



Glue down installation  
 under the patent DTU 51.2



Floating installation gluing TG  
 using plastic DPM and Isol 20 or  
 fully glue down using Presto PM



# DECLARATION OF PERFORMANCE

## N° 1019824



**Unique identification code of product-type:** Chevron 139 Tongue&Groove, 14 mm, French oak

**Intended use/es:** Engineered single plank made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

**Manufacturer:** PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

**System/s of Assessment and Verification of Constancy of Performance:** n°4

**Harmonised standard:** EN 14342 : 2013

### Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation	
Reaction of fire	Dfl-s1	EN 14342 : 2013	
Features for this classification: - Average minimum density (Kg/m <sup>3</sup> ) - Average thickness (mm) - Intended use, fitting mode	500 14 Floating fit		
Formaldehyde emission	E1		EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm		-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Class A+ < 1µg/m <sup>3</sup>	ISO 16000	
Breaking strength	N/A	-	
Slipperiness	N/A	-	
Thermal conductivity (W/m.K)	0.13	EN 14342 / Chapter 4.7	
Thermal resistance (m <sup>2</sup> .K/W)	0.108		
Biological sustainability	Class 1	EN 335	
RE2020 - Building Carbon Index	3 kg.CO <sub>2</sub> /m <sup>2</sup>	-	
FDES 2022 - Life Cycle impact assessment	8.6 kg éq. CO <sub>2</sub> /m <sup>2</sup>	-	

N/A : Not Applicate

\*VOC: Volatile Organic Compounds

\*\*CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025  
**Carole FRANÇOIS**

