



Elegant browns

PANAGET

manufacture française de parquet
DEPUIS 1929



N° 1019564

WALNUT SATIN, HERRINGBONE 139 TONGUE&GROOVE / 13 MM

Characteristics

Specie: Walnut **Origin:** Canada

Grade: - Grey brown to dark brown wood. Light and dark wood, knots, sapwood.

Finish: Satin - unbrushed, satin lacquered / Ecostrong satin lacquer - Gloss: 28/32

Design

Engineered single plank herringbone made under the patent EN 13489
Tongue&Groove



Description

Width: 139 mm

Length: 800 mm

Thickness: 13 mm

Top layer: 2.5 mm

Core: plywood

Counterbalance: unrolled wood

Profile: 4 bevels

Packaging

sqm/pack: 2.45

Pack/pallet: 32

sqm/pallet: 78.40

Weight/sqm: 7.4 kg

Weight/pallet: 580.2 kg



if installation and maintenance rules are followed

Installation method



Floating glued installation under the patent DTU 51.11




Glue down installation under the patent DTU 51.2



Floating installation gluing TG using plastic DPM and Isol 20 or fully glue down using Presto PM



*Emissions of volatile substances which could be toxic if inhaled. These are rated on scale from A+ (very low) to C (high).



Registration, Evaluation, Authorisation of Chemicals.



European Union Timber Regulation

PANAGET - 3 rue d'Orgères - 35230 Bourgbarré - FRANCE
tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // www.panaget.com



DECLARATION OF PERFORMANCE

N° 1019564

Unique identification code of product-type: Herringbone 139 Tongue&Groove, 13 mm, Walnut

Intended use/es: Engineered single plank made under the patent EN 13489
 Floating glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation
Reaction of fire	Dfl-s1	EN 14342 : 2013
Features for this classification: - Average minimum density (Kg/m ³) - Average thickness (mm) - Intended use, fitting mode	500 13 Floating fit	
Formaldehyde emission	E1	
Content of pentachlorophenol	PCP ≤ 5 ppm	-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Class A+ < 1µg/m ³	ISO 16000
Breaking strength	N/A	-
Slipperiness	N/A	-
Thermal conductivity (W/m.K)	0.13	EN 14342 / Chapter 4.7
Thermal resistance (m ² .K/W)	0.100	
Biological sustainability	Class 1	EN 335
RE2020 - Building Carbon Index	kg.CO ₂ /m ²	-
FDES 2022 - Life Cycle impact assessment	kg éq. CO ₂ /m ²	-

N/A : Not Applicate

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025

Carole FRANÇOIS