



Timeless natural hues

N° 1019712

FLAMED BEECH BOIS FLOTTÉ, DIVA 139 CLICK / 14 MM

Characteristics

Specie: Beech **Origin:** France

Grade: - Flamed red wood, light and dark wood, knots, all peculiarities accepted.

Finish: Bois flotté - brushed, matt lacquered with unfinished aspect / Ecostrong matt lacquer - Gloss: 4/6

Design

Engineered wide single plank made under the patent EN 13489
Click made under Unilin patent n°EP1640530



Description

Width: 139 mm
Length: 495 to 1992 mm
Thickness: 14 mm
Top layer: 3.4 mm
Core: HDF*
Counterbalance: unrolled wood
Profile: 4 bevels

*High Density Fiber board

Packaging

sqm/pack: 1.38
Pack/pallet: 55
sqm/pallet: 75.90
Weight/sqm: 11.6 kg
Weight/pallet: 880.4 kg



Installation method




Glue-free floating under
the patent DTU 51.11




Glue down installation
under the patent DTU 51.2



Collage en plein avec presto PM
uniquement.



*Emissions of volatile substances which could be toxic if inhaled. These are rated on scale from A+ (very low) to C (high).



DECLARATION OF PERFORMANCE

N° 1019712



Unique identification code of product-type: Diva 139 Click, 14 mm, Beech

Intended use/es: Engineered single plank made under the patent EN 13489
Glue-free floating under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation
Reaction of fire	Dfl-s1	EN 14342 : 2013
Features for this classification: - Average minimum density (Kg/m ³) - Average thickness (mm) - Intended use, fitting mode	500 14 Floating fit	
Formaldehyde emission	E1	
Content of pentachlorophenol	PCP ≤ 5 ppm	-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Class A+ < 1µg/m ³	ISO 16000
Breaking strength	N/A	-
Slipperiness	N/A	-
Thermal conductivity (W/m.K)	0.15	EN 14342 / Chapter 4.7
Thermal resistance (m ² .K/W)	0.093	
Biological sustainability	Class 1	EN 335
RE2020 - Building Carbon Index	3 kg.CO ₂ /m ²	-
FDES 2022 - Life Cycle impact assessment	8.6 kg éq. CO ₂ /m ²	-

N/A : Not Applicate

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025
Carole FRANÇOIS

