



Elegant browns

# PANAGET

manufacture française de parquet  
DEPUIS 1929



N° 1019714

## FLAMED BEECH CUIVRE, DIVA 139 CLICK / 14 MM

### Characteristics

**Specie:** Beech **Origin:** France

**Grade:** - Flamed red wood, light and dark wood, knots, all peculiarities accepted.

**Finish: Cuivre** - unbrushed, brown cooper tone matt oiled / Oil - Gloss: 5/8

For oiled wood floors, apply a thin coat of Panaget maintenance oil right after installation.

### Design

Engineered wide single plank made under the patent EN 13489

Click made under Unilin patent n°EP1640530



### Description

**Width:** 139 mm

**Length:** 495 to 1992 mm

**Thickness:** 14 mm

**Top layer:** 3.4 mm

**Core:** HDF\*

**Counterbalance:** unrolled wood

**Profile:** 4 bevels

\*High Density Fiber board

### Packaging

**sqm/pack:** 1.38

**Pack/pallet:** 55

**sqm/pallet:** 75.90

**Weight/sqm:** 11.6 kg

**Weight/pallet:** 880.4 kg



if installation and  
maintenance rules are  
followed

### Installation method



Glue-free floating under  
the patent DTU 51.11



Glue down installation  
under the patent DTU 51.2



Collage en plein avec presto PM  
uniquelement.



\*Emissions of volatile substances which could be  
toxic if inhaled. These are rated on scale from A+  
(very low) to C (high).



Registration, Evaluation,  
Authorisation of Chemicals.



European Union Timber  
Regulation

# DECLARATION OF PERFORMANCE

## N° 1019714



**Unique identification code of product-type:** Diva 139 Click, 14 mm, Beech

**Intended use/es:** Engineered single plank made under the patent EN 13489  
 Glue-free floating under the patent DTU 51.11

**Manufacturer:** PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

**System/s of Assessment and Verification of Constancy of Performance:** n°4

**Harmonised standard:** EN 14342 : 2013

### Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation	
Reaction of fire	Dfl-s1	EN 14342 : 2013	
Features for this classification: - Average minimum density (Kg/m <sup>3</sup> ) - Average thickness (mm) - Intended use, fitting mode	500 14 Floating fit		
Formaldehyde emission	E1		EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm		-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Class A+ < 1µg/m <sup>3</sup>	ISO 16000	
Breaking strength	N/A	-	
Slipperiness	N/A	-	
Thermal conductivity (W/m.K)	0.15	EN 14342 / Chapter 4.7	
Thermal resistance (m <sup>2</sup> .K/W)	0.093		
Biological sustainability	Class 1	EN 335	
RE2020 - Building Carbon Index	3 kg.CO <sub>2</sub> /m <sup>2</sup>	-	
FDES 2022 - Life Cycle impact assessment	8.6 kg éq. CO <sub>2</sub> /m <sup>2</sup>	-	

N/A : Not Applicate

\*VOC: Volatile Organic Compounds

\*\*CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025  
**Carole FRANÇOIS**

