



Elegant browns



N° 1017303

FRENCH OAK AUTHENTIC ARGILE, DIVA 223 TONGUE&GROOVE / 15 MM

Characteristics

Specie: French oak **Origin:** France

Grade: Authentic - Light and dark wood, black knots, filled knots, partially opened knots, traces of discolouration, black marks, cracks. This size of the knots is proportional to the width of the planks.

Finish: Argile - brushed, clay-tone matt lacquered / Ecostrong matt lacquer - Gloss: 4/6

Argile est une teinte à base de vieilliseur naturel qui agit sur le tanin du bois. Dans certains cas, une légère variation de teinte dans le temps peut être observée.

Design

Engineered extra-wide single plank made under the patent EN 13489 Tongue&Groove



Description

- Width:** 223 mm
- Length:** 700 to 2000 mm
- Thickness:** 15 mm
- Top layer:** 4.5 mm
- Core:** plywood
- Counterbalance:** unrolled wood
- Profile:** 2 bevels

Packaging

- sqm/pack:** 1.78
- Pack/pallet:** 39
- sqm/pallet:** 69.42
- Weight/sqm:** 10.9 kg
- Weight/pallet:** 756.7 kg



Installation method





Floating Glued installation under the patent DTU 51.11



Glue down installation under the patent DTU 51.2



Fully glue down using our special Presto PM glue.



DECLARATION OF PERFORMANCE

N° 1017303



Unique identification code of product-type: Diva 223 Tongue&Groove, 15 mm, French oak

Intended use/es: Engineered single plank made under the patent EN 13489

Floating Glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation	
Reaction of fire	Dfl-s1	EN 14342 : 2013	
Features for this classification: - Average minimum density (Kg/m ³) - Average thickness (mm) - Intended use, fitting mode	500 15 Floating fit		
Formaldehyde emission	E1		EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm		-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVPO910046A)	Class A+ < 1µg/m ³	ISO 16000	
Breaking strength	N/A	-	
Slipperiness	N/A	-	
Thermal conductivity (W/m.K)	0.15	EN 14342 / Chapter 4.7	
Thermal resistance (m ² .K/W)	0.100		
Biological sustainability	Class 1	EN 335	
RE2020 - Building Carbon Index	3 kg.CO ₂ /m ²	-	
FDES 2022 - Life Cycle impact assessment	8.6 kg éq. CO ₂ /m ²	-	

N/A : Not Applicate

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025
Carole FRANÇOIS

