



PANAGET

manufacture française de parquet
DEPUIS 1929



Timeless natural hues

N° 1016985

FRENCH OAK AUTHENTIC BOIS FLOTTÉ, DIVA 223 TONGUE&GROOVE / 15 MM

Characteristics

Specie: French oak **Origin:** France

Grade: Authentic - Light and dark wood, black knots, filled knots, partially opened knots, traces of discolouration, black marks, cracks. This size of the knots is proportional to the width of the planks.

Finish: Bois flotté - brushed, matt lacquered with unfinished aspect / Ecostrong matt lacquer - Gloss: 4/6

Design

Engineered extra-wide single plank made under the patent EN 13489
Tongue&Groove



Description

Width: 223 mm
Length: 700 to 2000 mm
Thickness: 15 mm
Top layer: 4.5 mm
Core: plywood
Counterbalance: unrolled wood
Profile: 2 bevels

Packaging

sqm/pack: 1.78
Pack/pallet: 39
sqm/pallet: 69.42
Weight/sqm: 10.9 kg
Weight/pallet: 756.7 kg



if installation and
maintenance rules are
followed

Installation method



Floating Glued
installation under the
patent DTU 51.11




Glue down installation
under the patent DTU 51.2



Fully glue down using our
special Presto PM glue.



*Emissions of volatile substances which could be
toxic if inhaled. These are rated on scale from A+
(very low) to C (high).



PANAGET - 3 rue d'Orgères - 35230 Bourgbarré - FRANCE
tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // www.panaget.com

DECLARATION OF PERFORMANCE

N° 1016985



Unique identification code of product-type: Diva 223 Tongue&Groove, 15 mm, French oak

Intended use/es: Engineered single plank made under the patent EN 13489

Floating Glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

| Essential features | Performances | Appropriate Technical Documentation and/or Specific Technical Documentation | |
|---|--|---|----------|
| Reaction of fire | Dfl-s1 | EN 14342 : 2013 | |
| Features for this classification: - Average minimum density (Kg/m ³) - Average thickness (mm) - Intended use, fitting mode | 500 15 Floating fit | | |
| Formaldehyde emission | E1 | | EN 717-1 |
| Content of pentachlorophenol | PCP ≤ 5 ppm | | - |
| Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVPO910046A) | Class A+ < 1µg/m ³ | ISO 16000 | |
| Breaking strength | N/A | - | |
| Slipperiness | N/A | - | |
| Thermal conductivity (W/m.K) | 0.15 | EN 14342 / Chapter 4.7 | |
| Thermal resistance (m ² .K/W) | 0.100 | | |
| Biological sustainability | Class 1 | EN 335 | |
| RE2020 - Building Carbon Index | 3 kg.CO ₂ /m ² | - | |
| FDES 2022 - Life Cycle impact assessment | 8.6 kg éq. CO ₂ /m ² | - | |

N/A : Not Applicate

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025
Carole FRANÇOIS

