



Timeless natural hues



N° 1022765

## FRENCH OAK AUTHENTIC TOPAZE HIGH TRAFFIC, DIVA 184 TONGUE&GROOVE / 14 MM

### Characteristics

**Specie:** French oak **Origin:** France

**Grade: Authentic** - Light and dark wood, black knots, filled knots, partially opened knots, traces of discolouration, black marks, cracks. This size of the knots is proportional to the width of the planks.

**Finish: Topaze High Traffic** - brushed, matt lacquered / Ecostrong matt lacquer - Gloss: 4/6

### Design

Engineered extra-wide single plank made under the patent EN 13489 Tongue&Groove



### Description

**Width:** 184 mm  
**Length:** 500 to 2000 mm  
**Thickness:** 14 mm  
**Top layer:** 3.4 mm  
**Core:** plywood  
**Counterbalance:** unrolled wood  
**Profile:** 4 bevels

### Packaging

**sqm/pack:** 1.84  
**Pack/pallet:** 44  
**sqm/pallet:** 80.96  
**Weight/sqm:** 7.4 kg  
**Weight/pallet:** 599.1 kg



### Installation method





Floating glued installation under the patent DTU 51.11



Glue down installation under the patent DTU 51.2



Floating installation gluing TG using plastic DPM and Isol 20 or fully glue down using Presto PM



# DECLARATION OF PERFORMANCE

## N° 1022765



**Unique identification code of product-type:** Diva 184 Tongue&Groove, 14 mm, French oak

**Intended use/es:** Engineered single plank made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

**Manufacturer:** PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

**System/s of Assessment and Verification of Constancy of Performance:** n°4

**Harmonised standard:** EN 14342 : 2013

### Declared performances:

| Essential features                             | Performances                               | Appropriate Technical Documentation and/or Specific Technical Documentation |
|--|--|---|
| Reaction of fire                               | Dfl-s1                                     | EN 14342 : 2013   |
| Features for this classification:              |  |   |
| - Average minimum density (Kg/m <sup>3</sup> ) | 500  |   |
| - Average thickness (mm)                       | 14   |   |
| - Intended use, fitting mode                   | Floating fit                               |   |
| Formaldehyde emission                          | E1   | EN 717-1  |
| Content of pentachlorophenol                   | PCP ≤ 5 ppm                                | -   |
| Release of other dangerous substances:         |  | ISO 16000   |
| - VOC* emissions (Decree No 2011-321)          | Class A+                                   |   |
| - CMR 1&2** emissions (Decree No DEVPO910046A) | < 1µg/m <sup>3</sup>                       |   |
| Breaking strength                              | N/A  | -   |
| Slipperiness                                   | N/A  | -   |
| Thermal conductivity (W/m.K)                   | 0.13                                       | EN 14342 / Chapter 4.7  |
| Thermal resistance (m <sup>2</sup> .K/W)       | 0.108                                      |   |
| Biological sustainability                      | Class 1                                    | EN 335  |
| RE2020 - Building Carbon Index                 | 3 kg.CO <sub>2</sub> /m <sup>2</sup>       | -   |
| FDES 2022 - Life Cycle impact assessment       | 8.6 kg éq. CO <sub>2</sub> /m <sup>2</sup> | -   |

N/A : Not Applicate

\*VOC: Volatile Organic Compounds

\*\*CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025  
**Carole FRANÇOIS**

