



Subtle greys

PANAGET

manufacture française de parquet
DEPUIS 1929



N° 1022061

FRENCH OAK CLASSIC SAPHIR, DIVA 223 TONGUE&GROOVE / 15 MM

Characteristics

Specie: French oak **Origin:** France

Grade: Classic - Light and dark wood, black knots, medular rays, traces of discolouration.

Finish: Saphir - brushed, white matt lacquered / Ecostrong matt lacquer - Gloss: 4/6

While we take the greatest care in manufacturing our flooring, there can sometimes be slight variations in colouring. So it's important to factor in margin 2-5% more than the actual you're covering. This means you won't run out of planks and will be sure to enjoy beautiful finished product.

Design

Engineered extra-wide single plank made under the patent EN 13489
Tongue&Groove



Description

Width: 223 mm

Length: 700 to 2000 mm

Thickness: 15 mm

Top layer: 4.5 mm

Core: plywood

Counterbalance: unrolled wood

Profile: 2 bevels

Packaging

sqm/pack: 1.78

Pack/pallet: 39

sqm/pallet: 69.42

Weight/sqm: 10.9 kg

Weight/pallet: 756.7 kg



if installation and
maintenance rules are
followed

Installation method



Floating glued
installation under the
patent DTU 51.11




Glue down installation
under the patent DTU 51.2



Fully glue down using our
special Presto PM glue.



*Emissions of volatile substances which could be
toxic if inhaled. These are rated on scale from A+
(very low) to C (high).



PANAGET - 3 rue d'Orgères - 35230 Bourgbarré - FRANCE
tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // www.panaget.com

DECLARATION OF PERFORMANCE

N° 1022061



Unique identification code of product-type: Diva 223 Tongue&Groove, 15 mm, French oak

Intended use/es: Engineered single plank made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation
Reaction of fire	Dfl-s1	EN 14342 : 2013
Features for this classification: - Average minimum density (Kg/m ³)	500	
- Average thickness (mm)	15	
- Intended use, fitting mode	Floating fit	
Formaldehyde emission	E1	EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm	-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Class A+ < 1µg/m ³	ISO 16000
Breaking strength	N/A	-
Slipperiness	N/A	-
Thermal conductivity (W/m.K)	0.15	EN 14342 / Chapter 4.7
Thermal resistance (m ² .K/W)	0.100	
Biological sustainability	Class 1	EN 335
RE2020 - Building Carbon Index	3 kg.CO ₂ /m ²	-
FDES 2022 - Life Cycle impact assessment	8.6 kg éq. CO ₂ /m ²	-

N/A : Not Applicate

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025
Carole FRANÇOIS

