



Elegant browns

PANAGET

manufacture française de parquet
DEPUIS 1929



N° 1019718

WALNUT SATIN, DIVA 139 TONGUE&GROOVE / 14 MM

Characteristics

Specie: Walnut **Origin:** Canada

Grade: - Grey brown to dark brown wood. Light and dark wood, knots, sapwood.

Finish: **Satin** - unbrushed, satin lacquered / Ecostrong satin lacquer - Gloss: 28/32

Design

Engineered wide single plank made under the patent EN 13489
Tongue&Groove



Description

Width: 139 mm
Length: 500 to 2000 mm
Thickness: 14 mm
Top layer: 3.4 mm
Core: plywood
Counterbalance: unrolled wood
Profile: 4 bevels

Packaging

sqm/pack: 1.39
Pack/pallet: 55
sqm/pallet: 76,45
Weight/sqm: 7.4 kg
Weight/pallet: 565.7 kg



Installation method




Floating glued
installation under the
patent DTU 51.11



Glue down installation
under the patent DTU 51.2



Floating installation gluing TG
using plastic DPM and Isol 20 or
fully glue down using Presto PM



*Emissions of volatile substances which could be toxic if inhaled. These are rated on scale from A+ (very low) to C (high).

GUARANTEE
30
YEARS
CONCEPTION



Registration, Evaluation,
Authorisation of Chemicals.

PANAGET - 3 rue d'Orgères - 35230 Bourgarré - FRANCE
tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // www.panaget.com

DECLARATION OF PERFORMANCE

N° 1019718



Unique identification code of product-type: Diva 139 Tongue&Groove, 14 mm, Walnut

Intended use/es: Engineered single plank made under the patent EN 13489
 Floating glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation	
Reaction of fire	Dfl-s1	EN 14342 : 2013	
Features for this classification: - Average minimum density (Kg/m ³) - Average thickness (mm) - Intended use, fitting mode	500 14 Floating fit		
Formaldehyde emission	E1		EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm		-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Class A+ < 1µg/m ³	ISO 16000	
Breaking strength	N/A	-	
Slipperiness	N/A	-	
Thermal conductivity (W/m.K)	0.13	EN 14342 / Chapter 4.7	
Thermal resistance (m ² .K/W)	0.108		
Biological sustainability	Class 1	EN 335	

N/A : Not Applicate

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025
Carole FRANÇOIS

