



Elegant browns

PANAGET

manufacture française de parquet
DEPUIS 1929



N° 1017303

FRENCH OAK AUTHENTIC ARGILE, DIVA 223 TONGUE&GROOVE / 15 MM Diva 223 - 8 3/4" TONGUE&GROOVE / 5/8

Characteristics

Species: French oak **Origin:** France

Grade: Authentic - Light and dark wood, black knots, filled knots, partially opened knots, traces of discolouration, black marks, cracks. This size of the knots is proportional to the width of the planks.

Finish: Argile - brushed, clay-tone matt lacquered / Ecostrong matt lacquer - Gloss: 4/6

Argile est une teinte à base de vieillisseur naturel qui agit sur le tanin du bois. Dans certains cas, une légère variation de teinte dans le temps peut être observée.

Design

Engineered extra-wide single plank made under the patent EN 13489
Tongue&Groove



Description

Width: 223 mm	8 3/4"
Length: 700 to 2000 mm	27" to 78"
Thickness: 15 mm	5/8"
Top layer: 4.5 mm	5
Core: plywood	
Counterbalance: unrolled wood	
Profile: 2 bevels	

Packaging

Pack/pallet: 39

sqm/pack: 1.78
sqm/pallet: 69.42

sqft/pack: 19.15
sqft/pallet: 747.23

Weight/sqm: 10.9 Kg
Weight/sqft: 1.01
Weight/pallet: 756.7 Kg



if installation and
maintenance rules are
followed

Installation method





Floating Glued
installation under the
patent DTU 51.11



Glue down installation
under the patent DTU 51.2



Fully glue down using our
special Presto PM glue.



PANAGET - 3 rue d'Orgères - 35230 Bourgbarré - FRANCE
tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // www.panaget.com

DECLARATION OF PERFORMANCE

N° 1017303



Unique identification code of product-type: Diva 223 Tongue&Groove, 15 mm, French oak

Diva 223 - 8 3/4" Tongue&Groove /5/8

Intended use/es: Engineered single plank made under the patent EN 13489

Floating Glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation
Reaction of fire	Dfl-s1	EN 14342 : 2013
Features for this classification: - Average minimum density (Kg/m³) - Average thickness (mm) - Intended use, fitting mode	500 15 Floating fit	
Formaldehyde emission	E1	
Content of pentachlorophenol	PCP ≤ 5 ppm	
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEV0910046A)	Class A+ < 1µg/m³	ISO 16000
Breaking strength	N/A	-
Slipperiness	N/A	-
Thermal conductivity (W/m.K)	0.15	EN 14342 / Chapter 4.7
Thermal resistance (m².K/W)	0.100	
Biological sustainability	Class 1	EN 335
RE2020 - Building Carbon Index	3 kg.CO₂/m²	-
FDES 2022 - Life Cycle impact assessment	8.6 kg éq. CO₂/m²	-

N/A : Not Applicate

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025

Carole FRANÇOIS

3 rue d'Orgères - 35230 Bourgbarré - FRANCE / tel: +33 (0)2 99 05 77 77 - fax: +33 (0)2 99 57 73 55

Entreprise dont le système qualité a été **certifié ISO 9001** par Bureau Veritas Certification.

SAS au capital de 4 957 200 € - RCS Rennes B 402 853 220 - Siret : 402 853 220 000 34 - APE : 1622 Z - n° TVA : FR 0640 2853220

www.panaget.com