



Timeless natural hues

PANAGET

manufacture française de parquet
DEPUIS 1929



N° 1019170

FRENCH OAK AUTHENTIC MIEL, DIVA 184 TONGUE&GROOVE / 14 MM Diva 7^{1/4}" TONGUE&GROOVE / 9/16"

Characteristics

Species: French oak **Origin:** France

Grade: Authentic - Light and dark wood, black knots, filled knots, partially opened knots, traces of discolouration, black marks, cracks. This size of the knots is proportional to the width of the planks.

Finish: Miel - brushed, natural matt lacquered / Ecostrong matt lacquer - Gloss: 4/6

Design

Engineered extra-wide single plank made under the patent EN 13489 Tongue&Groove



Description

Width: 184 mm	7 1/4"
Length: 500 to 2000 mm	19.5" to 78"
Thickness: 14 mm	9/16"
Top layer: 3.4 mm	4"
Core: plywood	
Counterbalance: unrolled wood	
Profile: 4 bevels	

Packaging

Pack/pallet: 44

sqm/pack: 1.84
sqm/pallet: 80.96

sqft/pack: 19.81
sqft/pallet: 871.64

Weight/sqm: 7.4 kg
Weight/sqft: 0.687 kg
Weight/pallet: 599.1 kg



Installation method




Floating glued installation under the patent DTU 51.11



Glue down installation under the patent DTU 51.2



Floating installation gluing TG using plastic DPM and Isol 20 or fully glue down using Presto PM



DECLARATION OF PERFORMANCE

N° 1019170



Unique identification code of product-type: Diva 184 Tongue&Groove, 14 mm, French oak

Diva 7^{1/4}" Tongue&Groove / 9/16"

Intended use/es: Engineered single plank made under the patent EN 13489
 Floating glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation	
Reaction of fire	Dfl-s1	EN 14342 : 2013	
Features for this classification: - Average minimum density (Kg/m ³) - Average thickness (mm) - Intended use, fitting mode	500 14 Floating fit		
Formaldehyde emission	E1		EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm		-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVPO910046A)	Class A+ < 1µg/m ³	ISO 16000	
Breaking strength	N/A	-	
Slipperiness	N/A	-	
Thermal conductivity (W/m.K)	0.13	EN 14342 / Chapter 4.7	
Thermal resistance (m ² .K/W)	0.108		
Biological sustainability	Class 1	EN 335	
RE2020 - Building Carbon Index	3 kg.CO ₂ /m ²	-	
FDES 2022 - Life Cycle impact assessment	8.6 kg éq. CO ₂ /m ²	-	

N/A : Not Applicate

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025
Carole FRANÇOIS

