PANAGET
manufacture française de parquet
DEPUIS 1929

Timeless natural hues

N° 1000028

FRENCH OAK AUTHENTIC TOPAZE, SONATE 90 TONGUE&GROOVE / 14 MM

Charateristics

Specie: French oak **Origin :** France

Grade: **Authentic** - Light and dark wood, black knots, filled knots, partially opened knots, traces of discolouration, black marks, cracks. The size of the knots is proportional to the width of the planks.

Finish: Topaze - brushed, matt lacquered / Matt lacquer - Brillance (gloss) : 4/6

Design

Solid wide single plank made under patent EN 13226
Tongue & Groove

Description

Width: 90 mm
Length: 400 to 1300 mm
Thickness: 14 mm
Top layer: 7,0 mm
Core:
Couterbalance: no
Profile: 4 bevels

Packaging

sqm/pack: 1,64
Pack/pallet: 32
sqm/pallet: 52,48
Weight/sqm: 10,7 kg
Weight/pallet: 561,5 kg

if installation and maintenance rules are followed

Class of use:

31 R6



Installation method

Glue down installation under the patent DTU 51.2

Fully glue down using our special Presto PM glue.

Fully glue down Presto PM



*Emissions of volatile substances which could be toxic if inhabled. These are rated on scale from A+ (very low) to C (high).

Registration, Evaluation, Authorisation of Chemicals.

PANAGET - 3 rue d'Orgères - 35230 Bourgbarré - FRANCE
tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // **www.panaget.com**

PANAGET
manufacture française de parquet
DEPUIS 1929

DECLARATION OF PERFORMANCE

N° 1000028

CE

Unique identification code of product-type: SONATE 90 Tongue&Groove, 14 mm, French oak

Intented use/es: Solid single plank made under the patent EN 13226

Glue down installation under the patent DTU 51.2

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	**Performances**	**Appropriate Technical Documentation and/or Specific Technical Documentation**
Reaction of fire	Dfl-s1	EN 14342 : 2013
Features for this classification: - Average minimum density (Kg/m3) - Average thickness (mm) - Intented use, fitting mode	 650 14 Glued to the subfloor	
Formaldehyde emission	E1	EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm	-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	 Classe A+ < 1µg/m^3	ISO 16000
Breaking strengthe	NPD	-
Slipperiness	NPD	-
Thermal conductivity (W/m.K)	0,17	EN 14342 / Chapter 4.7
Thermal resistance (m2.K/W)	0,082	
Biological sustainability	Class 1	EN 335
RE2020 - Building Carbon Index	3 kg.CO_2/m^2	-
FDES 2022 - Life Cycle impact assessment	8,6kg éq. CO_2/m^2	-

N/A : Not Applicate
**VOC: Volatile Organic Compounds*
***CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.*

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsability of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, 14 January 2026
Carole FRANÇOIS

3 rue d'Orgères - 35230 Bourgbarré - FRANCE / tel: +33 (0)2 99 05 77 77 - fax: +33 (0)2 99 57 73 55
Entreprise dont le système qualité a été **certifié ISO 9001** par Bureau Veritas Certification.
SAS au capital de 4 957 200 € - RCS Rennes B 402 853 220 - Siret : 402 853 220 000 34 - APE : 1622 Z - n° TVA : FR 0640 2853220
www.panaget.com