PANAGET
manufacture française de parquet
DEPUIS 1929

Timeless natural hues

N° 1006920

FRENCH OAK TRADITION SATIN, ORFÉO 139 CLICK / 14 MM

Characteristics

Specie: French oak **Origin:** France

Grade: **Tradition** - Light and dark wood, black knots, filled knots, partially opened knots, traces of discoloration, black marks, filled cracks, sapwood.

Finish: Satin - unbrushed, satin lacquered / Ecostrong satin lacquer - Gloss: 28/32

Design

Engineered two-strip made under the patent EN 13489
Click made under Unilin patent n°EP1640530



Description

Width: 139 mm
Length: 1500 mm
Thickness: 14 mm
Top layer: 3.4 mm
Core: HDF*
Counterbalance: unrolled wood
Profile: square edged

*High Density Fiber board

Packaging

sqm/pack: 1.46
Pack/pallet: 50
sqm/pallet: 73.00
Weight/sqm: 11.8 kg
Weight/pallet: 861.4 kg

KITCHEN COMPATIBLE
if installation and maintenance rules are followed

Installation method

Glue-free flo ting under the patent DTU 51.11

Glue down installation under the patent DTU 51.2

Floating installation using plastic DM and Isol 20 or fully glue down using Presto PM

Fully glue down Presto PM

PEFC Certified
This product is from sustainably managed forests and controlled sources
PEFC 10-35-39
www.pefc-france.org

PARQUETS DE FRANCE
PARQUETFRANÇAIS.ORG

EMISSIONS TO INSIDE AIR*
A+
A+ A B C
*Emissions of volatile substances which could be toxic if inhabited. These are rated on scale from A+ (very low) to C (high).

GUARANTEE 30 YEARS CONCEPTION

REACH COMPLIANCE
Registration, Evaluation, Authorisation of Chemicals.

100% French oak
designed with a French touch
PANAGET

PANAGET - 3 rue d'Orgères - 35230 Bourgbarré - FRANCE
tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // **www.panaget.com**

PANAGET
manufacture française de parquet
DEPUIS 1929

DECLARATION OF PERFORMANCE
N° 1006920

CE

Unique identification code of product-type: Orféo 139 Click, 14 mm, French oak

Intented use/es: Engineered single plank made under the patent EN 13489
Glue-free flo ting under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation
Reaction of fi e	Dfl-s	EN 14342 : 2013
Features for this classific tion: - Average minimum density (Kg/m³) - Average thickness (mm) - Intented use, fitting mode	 500 14 Floating fi	
Formaldehyde emission	E1	EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm	-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	 Class A+ < 1µg/m³	ISO 16000
Breaking strength	N/A	-
Slipperiness	N/A	-
Thermal conductivity (W/m.K)	0.15	EN 14342 / Chapter 4.7
Thermal resistance (m².K/W)	0.093	
Biological sustainability	Class 1	EN 335
RE2020 - Building Carbon Index	3 kg.CO_2/m²	-
FDES 2022 - Life Cycle impact assessment	8.6 kg éq. CO_2/m²	-

N/A : Not Applicate
**VOC: Volatile Organic Compounds*
***CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.*

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsability of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, January 27th 2025
Carole FRANÇOIS

3 rue d'Orgères - 35230 Bourgbarré - FRANCE / tel: +33 (0)2 99 05 77 77 - fax: +33 (0)2 99 57 73 55
Entreprise dont le système qualité a été **certifié ISO 9001** par Bureau Veritas Certific tion.
SAS au capital de 4 957 200 € - RCS Rennes B 402 853 220 - Siret : 402 853 220 000 34 - APE : 1622 Z - n° TVA : FR 0640 2853220
www.panaget.com