



Timeless natural hues

N° 1016618

## FRENCH OAK AUTHENTIC TOPAZE, HERRINGBONE 139 TONGUE&GROOVE / 14 MM

### Charateristics

**Specie:** French oak **Origin :** France

**Grade: Authentic** - Light and dark wood, black knots, filled knots, partially opened knots, traces of discolouration, black marks, cracks. The size of the knots is proportional to the width of the planks.

**Finish: Topaze** - brushed, matt lacquered / Matt lacquer - Brillance (gloss) : 4/6

### Design

Engineered single plank herringbone pattern made under patent EN 13489  
Tongue & Groove



### Description

**Width:** 139 mm  
**Length:** 800 mm  
**Thickness:** 14 mm  
**Top layer:** 3,4 mm  
**Core:** plywood  
**Couterbalance:** unrolled wood  
**Profile:** 4 bevels

### Packaging

**sqm/pack:** 2,22  
**Pack/pallet:** 32  
**sqm/pallet:** 71,04  
**Weight/sqm:** 7,4 kg  
**Weight/pallet:** 525,7 kg



**Class of use:**  
**31 R2**



### Installation method





Floating glued  
installation under the  
patent DTU 51.11



Glue down installation  
under the patent DTU 51.2



Floating installation using  
plastic DM and Isol 20 or fully  
glue down using Presto PM



PANAGET - 3 rue d'Orgères - 35230 Bourgarré - FRANCE  
tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // [www.panaget.com](http://www.panaget.com)



# DECLARATION OF PERFORMANCE

N° 1016618

**Unique identification code of product-type:** HERRINGBONE 139 Tongue&Groove, 14 mm, French oak

**Intended use/es:** Engineered single plank made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

**Manufacturer:** PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

**System/s of Assessment and Verification of Constancy of Performance:** n°4

**Harmonised standard:** EN 14342 : 2013

## Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation	
Reaction of fire	Dfl-s1	EN 14342 : 2013	
Features for this classification: - Average minimum density (Kg/m3) - Average thickness (mm) - Intended use, fitting mode	500 14 Floating fit		
Formaldehyde emission	E1		EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm		-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Classe A+ < 1µg/m <sup>3</sup>	ISO 16000	
Breaking strengthe	NPD	-	
Slipperiness	NPD	-	
Thermal conductivity (W/m.K)	0,13	EN 14342 / Chapter 4.7	
Thermal resistance (m2.K/W)	0,108		
Biological sustainability	Class 1	EN 335	
RE2020 - Building Carbon Index	3 kg.CO <sub>2</sub> /m <sup>2</sup>	-	
FDES 2022 - Life Cycle impact assessment	8,6kg éq. CO <sub>2</sub> /m <sup>2</sup>	-	

N/A : Not Applicate

\*VOC: Volatile Organic Compounds

\*\*CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, 14 January 2026  
**Carole FRANÇOIS**