



Timeless natural hues

N° 1017695

## FRENCH OAK MIX TOPAZE, ALTO 139X2010 CLICK UNIFIT / 12 MM

### Charateristics

**Specie:** French oak **Origin :** France

**Grade: Mix** - A lightly sorted grade, dedicated to stock ranges, representing a mix of our «Essential» grades. This combination ensures a warm and lively look.

**Finish: Topaze** - brushed, matt lacquered / Matt lacquer - Brillance (gloss) : 4/6

### Design

Engineered single plank finger-jointed made under patent EN 13489

Click made under Unilin patent n°EP2217787

1 twin & single-stave plank in mm = 1210 or 605 + 605 or 805 + 405 or 705 + 505



### Description

**Width:** 139 mm

**Length:** 2010 mm

**Thickness:** 12 mm

**Top layer:** 2,5 mm

**Core:** HDF\*

**Couterbalance:** unrolled wood

**Profile:** 2 bevels

\*High Density Fiber board

### Packaging

**sqm/pack:** 1,96

**Pack/pallet:** 45

**sqm/pallet:** 88,20

**Weight/sqm:** 9,9 kg

**Weight/pallet:** 873,2 kg



if installation and maintenance rules are followed

### Class of use:

31 R1



### Installation method



Glue-free floating under the patent DTU 51.11



Glue down installation under the patent DTU 51.2




Floating installation using plastic DM and Isol 20 or fully glue down using Presto PM



Fully glue down Presto PM



\*Emissions of volatile substances which could be toxic if inhaled. These are rated on scale from A+ (very low) to C (high).





# DECLARATION OF PERFORMANCE

N° 1017695

**Unique identification code of product-type:** ALTO 139 Click Unifit, 12 mm, French oak

**Intended use/es:** Engineered single plank made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

**Manufacturer:** PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

**System/s of Assessment and Verification of Constancy of Performance:** n°4

**Harmonised standard:** EN 14342 : 2013

## Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation	
Reaction of fire	Dfl-s1	EN 14342 : 2013	
Features for this classification: - Average minimum density (Kg/m3) - Average thickness (mm) - Intended use, fitting mode	500 12 Floating fit		
Formaldehyde emission	E1		EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm		-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Classe A+ < 1µg/m <sup>3</sup>	ISO 16000	
Breaking strengthe	NPD	-	
Slipperiness	NPD	-	
Thermal conductivity (W/m.K)	0,15	EN 14342 / Chapter 4.7	
Thermal resistance (m2.K/W)	0,080		
Biological sustainability	Class 1	EN 335	
RE2020 - Building Carbon Index	3 kg.CO <sub>2</sub> /m <sup>2</sup>	-	
FDES 2022 - Life Cycle impact assessment	8,6kg éq. CO <sub>2</sub> /m <sup>2</sup>	-	

N/A : Not Applicate

\*VOC: Volatile Organic Compounds

\*\*CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, 14 January 2026  
**Carole FRANÇOIS**