



Timeless natural hues



N° 1021455

FLAMED BEECH SATIN, HERRINGBONE 139 TONGUE&GROOVE / 14 MM

Charateristics

Specie: Flamed beech **Origin :** France

Grade: - Flamed red wood, light and dark wood, knots, all peculiarities accepted

Finish: Satin - unbrushed, satin lacquered / Satin lacquer - Brillance (gloss) : 28/32

Design

Engineered single plank herringbone pattern made under patent EN 13489
Tongue & Groove



Description

Width: 139 mm
Length: 800 mm
Thickness: 14 mm
Top layer: 3,4 mm
Core: plywood
Couterbalance: unrolled wood
Profile: 4 bevels

Packaging

sqm/pack: 2,22
Pack/pallet: 32
sqm/pallet: 71,04
Weight/sqm: 7,4 kg
Weight/pallet: 525,7 kg



Class of use:
31 R2



Installation method





Floating glued
installation under the
patent DTU 51.11



Glue down installation
under the patent DTU 51.2



Fully glue down using our
special Presto PM glue.





DECLARATION OF PERFORMANCE

N° 1021455

Unique identification code of product-type: HERRINGBONE 139 Tongue&Groove, 14 mm, Flamed beech

Intended use/es: Engineered single plank made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation	
Reaction of fire	Dfl-s1	EN 14342 : 2013	
Features for this classification: - Average minimum density (Kg/m3) - Average thickness (mm) - Intended use, fitting mode	500 14 Floating fit		
Formaldehyde emission	E1		EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm		-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Classe A+ < 1µg/m ³	ISO 16000	
Breaking strengthe	NPD	-	
Slipperiness	NPD	-	
Thermal conductivity (W/m.K)	0,13	EN 14342 / Chapter 4.7	
Thermal resistance (m2.K/W)	0,108		
Biological sustainability	Class 1	EN 335	
RE2020 - Building Carbon Index	3 kg.CO ₂ /m ²	-	
FDES 2022 - Life Cycle impact assessment	8,6kg éq. CO ₂ /m ²	-	

N/A : Not Applicate

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category.

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, 14 January 2026
Carole FRANÇOIS